

FrontSeller

The cooling pan for the front of the counter



IRE-	

More sales thanks to the additional beverage sales!

- For additional sales impulses at the point of sale
- Low space requirement
- **■** Easy installation

If you are hungry, you are often thirsty too

Therefore, you can offer delicious snacks and chilled drinks together in one place.

This is possible with the compact FrontSeller, which is placed directly in the customer's field of vision close to the cooled snacks.

Installation example FrontSeller 1200 with Snack-Counter COMBI

WIHA FrontSeller		Cooling power [-10°ET]
Model	ArtNo.	
FrontSeller 800	9185	170 W
FrontSeller 1200	9186	230 W

Description

Cooling pan with contact pipes for the sale of beverages and for the installation into the counter front.

Temperature range inside the pan: 4°C to 12°C (climate class 3: 25°C/ 60% relative humidity).

Storage capacity: FrontSeller 800: approx. 24 PET bottles 0.5 litre FrontSeller 1200: approx. 36 PET bottles 0.5 litre

Special Accessories

TMP 350 contoller for external cooling unit

Art.-No. 3310


Design

Interior pan and exterior made entirely of stainless steel, material 1.4301. Pan interior is finished with a defrost water drain (condensation drain) located in the middle. Piping on 4 sides of 8 mm OD copper. Pressure-injected polyurethane insulation (CFC-free). An expansion valve is integrated in the pan bottom behind an inspection panel.

Assembly is easy, because the pan can just be mounted into a vertical counter front. The FrontSeller is mounted into a rectangular counter recess and fixed with brackets on the rear. After installation, a circumferential frame covers the saw kerf.

Delivery includes:

- Intermediate shelf (CNS), perforated
- Pre-installed expansions valve for R134a/R513A
- Installation and operating instructions



The drawings are shown with special accessory that is not included; more drawings are available on www.wiha-web.com under "Info Centre / Customer Area".