for keeping food warm



Snack-Counter HOT KO

Heated display case with hotplate for a dry heat self-service version, the customer side is open







Snack-Counter HOT 520 KO	inte	1 rmediate	level			
Self-service version Height glass top 520 mm	round	angled	slanted	Width [mm]	Connection	
Snack-Counter HOT 520 KO - DT 1.5 **	25643	25644	25645	587	230V/1.65kW	
Snack-Counter HOT 520 KO - 2 *	25459	25463	25467	750	230V/2.05kW	
Snack-Counter HOT 520 KO - DT 2 **	25460	25464	25468	750	230V/2.05kW	
Snack-Counter HOT 520 KO - 3	25461	25465	25469	1075	230V/2.85kW	
Snack-Counter HOT 520 KO - 4	25462	25466	25470	1400	400V/3.75kW	

^{*} The maximum opening width is approx. 277 mm due to the sliding door. ** The operator side has wing doors instead of sliding doors.

	1 intermediate level				2					
Snack-Counter HOT 710 KO					intermediate levels					
Self-service version Height glass top 710 mm	round	angled	slanted	Width	Connection	round	angled	slanted	Width	Connection
Snack-Counter HOT 710 KO - DT 1.5 **	25646	25647	25648	587	230V/1.65kW	25649	25650	25651	587	230V/1.85kW
Snack-Counter HOT 710 KO - 2 *	25471	25475	25479	750	230V/2.05kW	25483	25487	25491	750	230V/2.3kW
Snack-Counter HOT 710 KO - DT 2 **	25472	25476	25480	750	230V/2.05kW	25484	25488	25492	750	230V/2.3kW
Snack-Counter HOT 710 KO - 3	25473	25477	25481	1075	230V/2.85kW	25485	25489	25493	1075	400V/2.9kW
Snack-Counter HOT 710 KO - 4	25474	25478	25482	1400	400V/3.75kW	25486	25490	25494	1400	400V/4.25kW

^{*} The maximum opening width is approx. 277 mm due to the sliding door.
** The operator side has wing doors instead of sliding doors.

Special Accessories Price label rail glass shelf GN 1.5 Price label rail glass shelf GN 2 Price label rail glass shelf GN 3 Price label rail glass shelf GN 4	ArtNo. 14000 14001 14002 14003
Price label rail lower display area GN 1.5 Price label rail lower display area GN 2	14004 14005
Price label rail lower display area GN 3 Price label rail lower display area GN 4	14006 14007

Description

Heated display case with hotplate to keep packaged food warm.

The merchandise displays are made of toughened black glass. The temperature is adjustable from approx. 30°C to approx. 75°C.

The customer side is open. Available with rounded, angled or slanted glass construction made of safety glass.

The operator side has sliding doors or wing doors.

All display levels are provided with a heat bridge and lighting. The intermediate shelves are equipped with a hotplate under the toughened black

Commercial product for the installation in stationary food and service counter.





for keeping food warm

Design

Inner surfaces and heat radiator are entirely made of stainless steel 1.4301 with ground surface.


The customer side is open. The side glass panes are made of safety glass. For even heating and for good illumination a heat bridge with shielded quart heat radiators and a possible of the level for the level of the level possible can be seen to the level of the level possible can be temperature of the heat bridges and the temperature of the lower hotplate can be


The digital thermostat for the hotplate and the infrared heat radiators is housed in an installation housing that is easy to maintain and can alternatively also be mounted in a counter front (cable length: approx. 1 m).


<u>Version DT</u>:
The operator side has wing doors made of insulating glass.


Otherwise: The operator side has sliding doors made of insulating glass, easily removable for cleaning (without bottom rail).



















More drawings are available on www.wiha-web.com under "Info Centre / Customer Area".