

FrontSeller XL

Bottle cooler with bottle slide

Note:
Also available in BLACK.

1
Straight
Installation



Preferred application:
Sale of beverages in the area of sales counters, food serving points or other points of sale.



Fan-assisted (circulating air) bottle cooler FrontSeller XL

- Optimal presentation of the beverages on a bottle slide (first in – first-out)
- Outstanding capacity of approx. 150 bottles
- Individual adjustable divider bars (3,5 mm grid)
- Highly luminous lighting track
- Simple refill from operator's side
- Lifiable evaporator for an easy and fast cleaning
- Highly effective refrigeration due to air curtain technology
- Comfortable digital temperature and defrosting controller



WIHA FrontSeller XL	For external cooling unit	With cooling unit and controller	Cooling power [-10°ET]	Connection cooling unit	Powder Coating Black
Model	Art.-No.	Art.-No.			Art.-No.
FrontSeller XL 800	30358	30359 *	450 W	230V/350W	30373
FrontSeller XL 1000	30305	30304 *	450 W	230V/350W	30356

The FrontSeller XL for external cooling units include an expansion valve for R134a / R513A and built-in temperature sensors.
* Without base element, the cooling unit is connected via refrigerant couplings.

Optimal presentation of the beverages

Fan-assisted bottle cooler for strong consumer sales for the installation into sales counters.

All bottles are inclined towards the customer for an enhanced presentation of the beverages. A specially designed merchandise display with an integrated slide ensures the replacement of sold bottles (first in – first out) and the customer view on a full assortment up to the last bottle.

The refill of the unit is notably user-friendly as all bottles are arranged on one drawer, accessible from the operator's side. Simply pull out the drawer, refill and push the drawer back into the origin position.

The 3.5 mm grid of the merchandise display enables the adjustment of the divider bars to match the size of the bottles.


WIHA Air Duct Housing UTB 60 for FrontSeller XL



WIHA Air Duct Housing UTB 60, panel left

Machine housing with cooling unit for the FrontSeller XL with ventilation system for supply and exhaust air on the operator side. Delivery including cooling unit type 450, left-mounted panel with controller TMP 620 and refrigerant couplings and 1.5 m long connection cables.

Art.-No.
7410



WIHA Air Duct Housing UTB 60, panel right

Machine housing with cooling unit for the FrontSeller XL with ventilation system for supply and exhaust air on the operator side. Delivery including cooling unit type 450, right-mounted panel with controller TMP 620 and refrigerant couplings and 1.5 m long connection cables.

Art.-No.
7411

1. Air Chiller Units

straight installation



1

Straight Installation

Special Accessories

Divider bar for bottle slide 770
TMP 620 controller for external cooling unit

Art.-No.

26458
12201

Art.-No.

Nighttime cover FrontSeller XL 800, lockable
Nighttime cover FrontSeller XL 1000, lockable

30368
30369

Description

Bottle cooler with circulating air for cooling beverages in bottles up to a height of 225 mm.

Temperature: < 12°C at 25°C/60% relative humidity (climate class 3 according to DIN EN ISO 23953).

Commercial product for the installation in stationary food and service counter.

For external cooling unit

Delivery includes:

- Expansion valve for R134a / R513A
- 12 pcs. divider bars
- Drain fitting with hose
- Built-in defrost and temperature sensor

Design

Interior pan is made entirely of stainless steel and is finished with flush threaded drain fitting (1 1/4"). Pressure-injected expanded polyurethane insulation (CFC-free). The exterior is made of galvanised sheet steel with ground surface. Inside the pan is a generously sized circulating air evaporator with coated surface and quiet low-voltage ventilators (12 V DC) for air circulation.

The drawer with the integrated bottle slide is mounted on stainless steel telescopic guides and can be pulled out easily. The complete drawer can be lifted out of the corpus after it has been fully pulled out into its end position. Following the removal of the drawer, the evaporator with air baffles and fans can be folded upwards and locked in the top position via gas pressure springs to give access to the cooling pan for an easy cleaning.

Cooling Unit Model

The cooling unit is fully pre-assembled and is connected to the cooling pan with refrigerant couplings. It comes with the TMP 620 built-in controller that is connected to the cooling unit and cooling pan via cable connectors. A freely usable output can be used for counter lighting.

The counter design should include a well-ventilated base unit for the cooling unit, located laterally next to the built-in cooling module.

With WIHA-LONG-LIFE for a longer operating life of the cooling unit.



The pulled-out drawer on operator's side allows a quick and easy refill with bottles.



Thanks to the bottle slide, a full range of bottles is always present in the viewing and removal area on the customer side.

